

TECHNOLOGIES SPECIFICATIONS

Vehicle type		CA3312	CA3313
Drive mode		8×4	8×5
Cab		New J5P - Flat roof / King row/Full floating	New J6P - Flat roof / King row/Full floating
Engine	Model	WEICHAH WP10.380E32	WEICHAH WP12.420E32
	Displacement (L)	9.726	11.596
	Maximum power (hp)	380	420
	Rated speed (rpm)	2,200	2,200
	Maximum torque/speed (Nm/rpm)	1250/(1500-1800)	1750/(1300-1600)
	Emission	EUROII	EUROII
Transmission	Model	FAST 12JSD160T	FAST 12JSD200T
	Form/number of gears	Manual/12	Manual/12
	Forward gear ratio coverage	15.53-1.0	15.53-1.0
Front axle load (kg)		9000	
Front suspension		Multiple leaf spring	Parabolic Leaf Springs with Shock Absorber
Rear axle load (kg)		2×16000	2×16001
Rear suspension		Multiple leaf spring	Parabolic Leaf Springs
Rear axle model/speed ratio		φ300/5.921	φ300/5.922
Chassis weight (kg)		13900	14000
Wheel base (mm)		1860+3960+1350	1860+3700+1350
Truck bed dimension (mm)		7600 x 2300 x 1400	760 x 2300 x 1600
Tire		12.00R20-18	13R22.5-18
Brake system		Drum brake, optional ABS	