

## Technical Specification

|                          |                          |                                     |
|--------------------------|--------------------------|-------------------------------------|
| Vehicle type             |                          | CA3250                              |
| Drive mode               |                          | 6×4                                 |
| Cab                      |                          | J6P Flat-top cab                    |
| Engine                   | Model                    | CA6DM2-42E52                        |
|                          | Displacement(L)          | 11.05                               |
|                          | Maximum power(hp)        | 420hp                               |
|                          | Rated speed(rpm)         | 1300rpm                             |
|                          | Maximum torque(Nm)       | 2100N.m                             |
|                          | Emission                 | EURO V                              |
| Transmission             | Model                    | ZF16S2230TO                         |
|                          | Form/number of gears     | 16                                  |
|                          | Forward gear ratio range | 0.84-13.8                           |
| Front axle load (kg)     |                          | 9000                                |
| Front suspension         |                          | 12 leafs                            |
| Rear axle load (kg)      |                          | 16000                               |
| Rear suspension          |                          | 13 leafs                            |
| Rear axle model          |                          | Φ300 cast iron wheel reducer bridge |
| Chassis self weight (kg) |                          | 10853                               |
| Towing Weight (kg)       |                          | 14100                               |
| Wheel base (mm)          |                          | 3800+1450                           |
| Saddle                   |                          | —                                   |
| Tire                     |                          | 12.00R24 20PR                       |
| Brake system             |                          | Drum Brake                          |
| Market Segment           |                          | Engineering Constrcution            |
|                          |                          |                                     |